

This Page Is Inserted by IFW Operations  
and is not a part of the Official Record

## **BEST AVAILABLE IMAGES**

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images may include (but are not limited to):

- BLACK BORDERS
- TEXT CUT OFF AT TOP, BOTTOM OR SIDES
- FADED TEXT
- ILLEGIBLE TEXT
- SKEWED/SLANTED IMAGES
- COLORED PHOTOS
- BLACK OR VERY BLACK AND WHITE DARK PHOTOS
- GRAY SCALE DOCUMENTS

**IMAGES ARE BEST AVAILABLE COPY.**

**As rescanning documents *will not* correct images,  
please do not report the images to the  
Image Problem Mailbox.**



[Log On](#) | [New File](#) | [Reset Sources](#)

[My Account](#) | [Products](#)

[Search: Quick/Number](#) | [Boolean](#) | [Advanced](#) | [Derwent](#)

**RESEARCH**

**PRODUCTS**

**INSIDE DELPHION**

## The Delphion Integrated View

Get Now: ☒ PDF | [More choices...](#)

Tools: Add to Work File: [Create new Wor](#)

View: [INPADOC](#) | Jump to: [Top](#) ☐ Go to: [Derwent](#)

☐ Email

**Title: JP8119708A2: INORGANIC BOARD AND ITS PRODUCTION**

**Derwent Title:** Inorganic plates for roof materials for improved bending strength - contg. fibres as sulphate-bleached pulp of broad-leaves or sulphate non-bleached trees, for tiles for improved freeze resistance ([Derwent Record](#))

**Country:** JP Japan

**Kind:** A (See also: [JP3282930B2](#) )

**Inventor:** SUZUKI SHINICHI;  
WATANABE HIROSHI;

**Assignee:** MATSUSHITA ELECTRIC WORKS LTD  
[News, Profiles, Stocks and More about this company](#)

**Published / Filed:** 1996-05-14 / 1994-10-26

**Application Number:** JP1994000262963

**IPC Code:** [C04B 28/02](#); [B28C 5/40](#); [C04B 38/00](#); [D21J 1/00](#); [C04B 28/02](#); [C04B 111/12](#);

**ECLA Code:** [C04B24/18](#); [C04B28/00](#);

**Priority Number:** 1994-10-26 JP1994000262963

**Abstract:** PURPOSE: To obtain an inorganic board excellent in flexural strength, freezing resistance and shock resistance.  
CONSTITUTION: This inorganic board is composed of cement as the main component and together with at least one selected from bleached and unbleached sulfate pulp of broadleaf tree. The bleached and the unbleached sulfate pulp of broadleaf tree of this process have 60% of fibers of 5-30µm in fiber diameter and 0.2-1.0mm in fiber length based on the total number of the fibers. Therefore, the ratio of fibers having an extremely short fiber or an extremely thin fiber is small, and accordingly the reinforcing effect for cement is kept in an adequately high level.  
COPYRIGHT: (C)1996,JPO

**INPADOC** None **Get Now:** [Family Legal Status Report](#)

**Legal Status:**

**Family:** [Show 2 known family members](#)

**Other Abstract Info:** CHEMABS 125(08)093902H CAN125(08)093902H DERABS C96-283272  
DERC96-283272

